
RIDILUX





Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150 Im/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising,





IP65

"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V **DALI**



▼ Technical Data (full sery)


Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-01A-100	φ260XH150mm	100 W	>80	2700-6000K	15000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	1.50 kgs

I + Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has 3 different sizes from 100-200W.

▼ Installation Method





▼ Photos





