RIDILUX

LED HIGH BAY



▼ Charaterastic

Power Up Any Space


1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150 $\mbox{Im/W}).$

2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.

3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.

4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.

+Loop, ceiling mounting and wall mounting +Working temperature is -50°C to 70°C



Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.



"Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



```
DALI
```

Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-01B-150	φ310XH156mm	150 W	>80	2700-6000K	22500 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	2.20 kgs
I +Notes: 1. Finish: Black, and customized RAL available 2. It has 3 different sizes from 100-200W.										

Installation Method



