

▼ Charaterastic

Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150-180 Im/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C







▼ Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.




ON/OFF

0-10V

DALI




▼ Family Matrix (Three difference size)



D (mm)	H (mm)	Watt
φ 250	155	100
φ 310	165	150
φ 360	175	200

▼ Installation Method














▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-02A-100	φ250XH155mm	100 W	>80	3000-6000K	15000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	1.80 kgs
HB-02B-150	φ310XH165mm	150 W	>80	3000-6000K	22500 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	2.20 kgs
HB-02C-200	φ360XH175mm	200 W	>80	3000-6000K	30000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	3.10 kgs

- I+Notes:
 1. Finish: Black, and customized RAL available
 2. It has 3 different sizes from 100-200W.

▼ Naming scheme




HB: Highbay RL: Road Light WW: Wall Washer LL: Linear Light Neon: LED strip light



▼ Charaterastic

Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150~180 lm/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I+Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.





IP65

"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V DALI



▼ Technical Data (full sery)


Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-02A-100	φ250XH155mm	100 W	>80	3000-6000K	15000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	1.80 kgs

I+Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has 3 different sizes from 100-200W.

▼ Installation Method














▼ Charaterastic

Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150~180 lm/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I+Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V DALI



▼ Technical Data (full sery)


Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-02B-150	φ310XH165mm	150 W	>80	3000-6000K	22500 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	2.20 kgs

I+Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has 3 different sizes from 100-200W.

▼ Installation Method














▼ Charaterastic

Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 150~180 lm/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I+Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V DALI



▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-02C-200	φ360XH175mm	200 W	>80	3000-6000K	30000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	3.10 kgs

I+Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has 3 different sizes from 100-200W.

▼ Installation Method



