
RIDILUX





Power Up Any Space

- 1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 130-180 Im/W).
- 2.Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V DALI



▼ Technical Data (full sery)


| Model | SIZE (mm) | POWER (W/M) | CRI | CCT (K) | LUMINOUS | VOLT | Control | Beam Angle | PF | N.W |
|------------|--------------|----------------|-----|------------|----------|-------------|------------------|------------|------|----------|
| HB-03B-150 | φ265XH150mm | 150 W | >80 | 3000-6000K | 19320 LM | 100-277V AC | On/Off or Dim | 60/90/120° | > 95 | 2.70 kgs |

I +Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has five different sizes from 60-400W.

▼ Installation Method





▼ Photos

