
RIDILUX





Power Up Any Space

- 1. Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 130~180 lm/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



▼ Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising,







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, PIs confirm before ordering.



ON/OFF 0-10V DALI



▼ Technical Data (full sery)


Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-03C-200	φ300XH150mm	200 W	>80	3000-6000K	25820 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	3.20 kgs

I + Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has five different sizes from 60-400W.

▼ Installation Method





▼ Photos



