
# **RIDILUX**





### **Power Up Any Space**

- 1. Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 130~180 lm/W).
- 2. Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.
- 3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.
- 4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.
- +Loop, ceiling mounting and wall mounting
- +Working temperature is -50°C to 70°C



# **▼** Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising,







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, PIs confirm before ordering.



ON/OFF 0-10V DALI



## ▼ Technical Data (full sery)


| Model      | SIZE<br>(mm) | POWER<br>(W/M) | CRI | CCT (K)    | LUMINOUS | VOLT        | Control          | Beam Angle | PF   | N.W      |
|------------|--------------|----------------|-----|------------|----------|-------------|------------------|------------|------|----------|
| HB-03D-300 | φ460XH140mm  | 300 W          | >80 | 3000-6000K | 45000 LM | 100-277V AC | On/Off or<br>Dim | 60/90/120° | > 95 | 4.50 kgs |

#### I + Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has five different sizes from 60-400W.

## **▼** Installation Method





#### **▼** Photos



