# RIDILUX

# LED HIGH BAY



## ▼ Charaterastic

#### Power Up Any Space


1.Durable & Efficient: Built-to-last design & LEDs deliver long life (50,000 hrs) & high output (up to 130~180 lm/W).

2.Sharp Focus, Happy Eyes: Precise optics provide bright, comfortable light with glare control.

3. Future-Proof Smart Control: Integrates with Interact software for adaptable lighting management.

4. Versatile Applications: Ideal for warehouses, factories, stores, restaurants, sports centers, and more.

+Loop, ceiling mounting and wall mounting +Working temperature is -50°C to 70°C



### Application

I+Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.



"Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



```
ON/OFF 0-10V DALI
```

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-03E-400	φ490XH140mm	400 W	>80	3000-6000K	60000 LM	100-277V AC	On/Off or Dim	60/90/120°	> 95	4.90 kgs
I +Notes: 1. Finish: Black, and customized RAL available 2. It has five different sizes from 60-400W.										

#### Installation Method

MAX A NHINED EN TO



