
RIDILUX



▼ Charaterastic

Durable LED Light with Improved Efficiency

- 1.Built to Last: Aluminum body with anti-glare design for comfortable lighting.
- 2. Efficient Heat Dissipation: Dual-cavity heat dissipation ensures long lifespan.
- 3. Sharp Light Distribution: Precise optics provide accurate illumination (combines 5).
- 4. Versatile Applications: Suitable for warehouses, factories, and more (combines 6).
- +Loop, ceiling mounting and wall mounting +Working temperature is -50°C to 70°C



▼ Application

I + Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising,







"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.



ON/OFF 0-10V

DALI



▼ Technical Data (full sery)


Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-05A-100	φ280XH149mm	100 W	>80	3000-6000K	15000 LM	100-277V AC	On/Off or Dim	90/120°	> 95	2.70 kgs

I + Notes:

- 1. Finish: Black, and customized RAL available
- 2. It has three different sizes from 100-200W.

▼ Installation Method





▼ Photos





