
RIDILUX

LED HIGH BAY





Application

dimmable.

▼ Charaterastic

Brighten Any Space Efficiently

high output efficacy(150lm/w).

+Loop, ceiling mounting and wall mounting +Working temperature is -50°C to 70°C

I+Warehouses, factories, exhibition halls, airports, gymnasiums, subway stations, outdoor advertising, etc.

1. Durable & Efficient: Built-to-last aluminum housing with efficient heat dissipation ensures long life and

2.Sharp Light Distribution: Advanced optics provide accurate light distribution for improved visibility.3.Versatility & Savings: Ideal for warehouses, factories, and more. Replaces up to a 480W HID and is



"Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



```
Microwave
Sensor
```

Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
HB-07B-100	φ350XH307mm	100 W	>70	3000-6000K	12000 LM	100-277V AC	On/Off or Dim	45/90/120°	> 95	3.40 kgs
I+Notes: 1. Finish: Black, and customized RAL available 2. It has five different sizes from 60-240W.										

Installation Method



