



IP66

- + Pole mounting or wall mounting
- + Working temperature is -50°C to 70°C

Charaterastic

Illuminate Your Space with Confidence:

- 1.Sleek & Durable Design:** Modern industrial aesthetic with a high-strength, impact-resistant aluminum body ensures a long-lasting impression.
- 2.Advanced Thermal Management:** Isolated dual-cavity design and independent radiator keep LEDs cool for optimal performance and longevity.
- 3.Exceptional Efficiency & Reliability:** High-voltage isolated drive prevents flickering and damage from voltage fluctuations, while high-efficiency LEDs provide superior brightness, energy savings, and slow brightness decay over time.

Application

I + Outdoor Occasion such as stadium/sport, wharve, airport and etc.

"Non-dim/dim" and "Mono/Tunable white/chromatic" is available, PIs confirm before ordering.



ON/OFF 0-10V DALI

Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
SL-01C	665X811X885mm	1500 W	>80	2700-5700K	217500 LM	100-277V AC	On/Off or Dim	15/30/45/60/120°	> 95	40.50 kgs

- I + Notes:
1. Finish: Black, and customized RAL available
 2. It can be changed into 4 basic combinations from 500W-2000W.

Simulation



Project



Photometric curve

