

IP66

▼ Charaterastic

Effortless Smart Lighting for Cities

1. Smart & Efficient: Integrates with smart city systems, offers wide power/color options (100W-300W, 3000K-6000K), and boasts high efficiency (up to 130 lm/W).
2. Durable Design: Modern, high-strength aluminum body (IP66 & IK10) resists impact, dust, and moisture.
3. Advanced Cooling: Dual-cavity system ensures optimal LED performance and lifespan.
4. Precise Light: Professional optics deliver accurate light distribution for safety and comfort.
5. Effortless Upkeep: Tool-free access and adjustable tilt simplify maintenance.

- ✦ Pole mounting.
- ✦ Working temperature is -50°C to 70°C

▼ Application

✦ Outdoor Occasion such as Urban main road, secondary road, branch road, industrial park road lighting, etc

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



Mono

ON/OFF 0-10V DALI

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
RL-01C-200	589X280X75mm	200 W	>80	2700-6000K	27000 LM	100-277V AC	On/Off or Dim	T3M / T4M	95	4.40 kgs
RL-01C-240	589X280X75mm	240 W	>80	2700-6000K	32400 LM	100-277V AC	On/Off or Dim	T3M / T4M	95	4.60 kgs

✦ Notes:

1. Finish: Black, and customized RAL available
2. It has four different size from 100W-300W.


▼ Project




▼ Photos



▼ Photometric curve



T3M



T4M