



▼ Characteristic


Effortless Smart Lighting for Cities

1. Smart & Efficient: Integrates with smart city systems, offers wide power/color options (30W-240W, 3000K-6000K), and boasts high efficiency (up to 160 lm/W).
2. Durable Design: Modern, high-strength aluminum body (IP66 & IK10) resists impact, dust, and moisture.
3. Advanced Cooling: Dual-cavity system ensures optimal LED performance and lifespan.
4. Precise Light: Professional optics deliver accurate light distribution for safety and comfort.
5. Effortless Upkeep: Tool-free access and adjustable tilt simplify maintenance.

- + Pole mounting.
- + Working temperature is -50°C to 70°C

▼ Application

I+ This product is suitable for: urban trunk roads, secondary trunk roads, branch roads, road lighting in industrial parks, etc.



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.

Mono ON/OFF 0-10V DALI

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
RL-03E-200	740X276X75mm	200 W	>80	3000-6000K	32000 LM	AC100-277V	ON/OFF	T2M	>0.95	2.50 kgs
RL-03E-240	740X276X75mm	240 W	>80	3000-6000K	38400 LM	AC100-277V	ON/OFF	T2M	>0.95	2.70 kgs

I+Notes:

1. Finish: Gray, and customized RAL available
2. It has five different size from 30W-240W.

▼ Project



▼ Photos



▼ Photometric curve

