
RIDILUX



((



IP66



▼ Charaterastic

Effortless Smart Lighting for Cities:

- 1.Smart & Efficient: Integrates with smart city systems, offers wide power/color options (100W-300W, 3000K-6000K), and boasts high efficiency (up to 130 lm/W).
- 2.Durable Design: Modern, high-strength aluminum body (IP66 & IK10) resists impact, dust, and moisture.
- 3.Advanced Cooling: Dual-cavity system ensures optimal LED performance and lifespan.
- 4. Precise Light: Professional optics deliver accurate light distribution for safety and comfort.
- 5. Effortless Upkeep: Tool-free access and adjustable tilt simplify maintenance.

▼ Application

 $I + Outdoor\ Occasion\ such\ as\ Urban\ main\ road,\ secondary\ road,\ branch\ road,\ industrial\ park\ road\ lighting,\ etc$

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, PIs confirm before ordering.

Mono

ON/OFF 0-10V

DALI

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
RL-05C-150	600*200*83mm	150W	>80	3000-6500K	110-120	AC85-320V	ON/OFF	105°	>0.95	

- I **+** Notes:
 - 1. Finish: Black, and customized RAL available
 - 2. It has four different sizes from 50W-250W.

▼ Project



▼ Photos



RIDILUX

▼ Photometric curve

