




IP66



▼ Charaterastic

Built to Last & Shine Bright

1. Cool Operation: Airflow design prevents overheating and ensures long LED lifespan.
2. Rugged Construction: High-grade aluminum housing with a protective coating resists impact, dust, and moisture.
3. Advanced Heat Dissipation: Dual-chamber design isolates heat sources for optimal performance.
4. Reliable & Efficient: High-voltage protection and efficient LEDs deliver long life and brightness even with fluctuating power grids.

- + Pole mounting or wall mounting
- + Working temperature is -50°C to 70°C

▼ Application

I+ Outdoor Occasion such as stadium/sport, wharve, airport and etc.

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI

▼ Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
SL-04A-72	200X200X233mm	72 W	>80	3000-5700K	12600 LM	AC90-305V	On/Off or Dim	120°	>0.95	4.80 kgs
SL-04A-100	200X200X233mm	100 W	>80	3000-5700K	17500 LM	AC90-305V	On/Off or Dim	120°	>0.95	4.80 kgs

I+Notes:

1. Finish: Black, and customized RAL available
2. It has two size with 4 different watt from 72W-200W, also can make different head combination.

▼ Simulation



▼ Project



▼ Photometric curve

