




▼ Charaterastic

Shine Smarter: The Future of Stadium Lighting

- 1.Precise & Sustainable: Minimizes light spill and glare, uses replaceable parts, and boasts plastic-free packaging for eco-friendly illumination.
- 2.Smart & Future-Proof: Integrates with smart cities, allows for upgrades, and features a modular design for easy maintenance.
- 3.Durable & Adjustable: Built to last with a weatherproof housing, and offers adjustable light levels for optimal use.
- +Pole mounting or wall mounting +Working temperature is -50°C to 70°C







▼ Application

 $\label{eq:continuous} \texttt{I} + \texttt{Outdoor} \ \texttt{Occasion} \ \texttt{such as stadium/sport}, \ \texttt{wharve}, \ \texttt{airport} \ \texttt{and} \ \texttt{etc.}$

"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, PIs confirm before ordering.



ON/OFF

▼ Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
SL-05D-200	416X352X58mm	200 W	>80	3000-6000K	26000 LM	AC100-265V	ON/OFF	30/60/90/120°	>0.95	4.60 kgs

I + Notes:

- Finish: Gray, and customized RAL available
 It has six size with 6 different watt from 50W-400W.

▼ Simulation

▼ Project





Photometric curve

