LED FLOOD LIGHT

RIDILUX



▼ Charaterastic

Shine Smarter: The Future of Stadium Lighting

1.Precise & Sustainable: Minimizes light spill and glare, uses replaceable parts, and boasts plastic-free packaging for eco-friendly illumination.


2.Smart & Future-Proof: Integrates with smart cities, allows for upgrades, and features a modular design for easy maintenance.

3.Durable & Adjustable: Built to last with a weatherproof housing, and offers adjustable light levels for optimal use.

+Pole mounting or wall mounting
+Working temperature is -50°C to 70°C

Application

I+Outdoor Occasion such as stadium/sport, wharve, airport and etc.





"Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, PIs confirm before ordering.

Mono ON/OFF

Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS	VOLT	Control	Beam Angle	PF	N.W
SL-05F-400	490X520X65mm	400 W	>80	3000-6000K	52000 LM	AC100-265V	ON/OFF	30/60/90/120°	>0.95	8.30 kgs
I + Notes: 1. Finish: Gray, and customized RAL available										

2. It has six size with 6 different watt from 50W-400W.

Simulation

▼ Project





Photometric curve

