


Standard without visor



With visor



▼ Charaterastic

- ✦ The lamp emphasizes the spatial effect of the building, enhances the customer's sense of space, adopts the structural waterproof design, and the performance is more stable.
- ✦ Aluminum housing ,ultra white tempered safety glass, lens -PMMA; vertically tilt mounting bracket; Transparent surface - imported weather resistant PU glue potting waterproof;
- ✦ Adopt military grade three hard anodizing process, thermal conductivity 230W/M*K anti-UV polyester powder, outdoor grade spray painting, conventional anti-UV5 protection.
- ✦ Surface mounting.
- ✦ Working temperature is -50°C to 70°C

▼ Application

- ✦ **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel
- ✦ **Urban:** Administrative Building , Commercial Building , Hotel , Mall
- ✦ **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM)	B.angle	VOLT	Control	Remark
WW-01A-24 1000mm	W37*H28.7mm	24 W	>80	Mono(2700-6000K) R/G/B/A	1632 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	24*1, Visor optional
WW-01A-12 500mm	W37*H28.7mm	12 W	>80	Mono(2700-6000K) R/G/B/A	816 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	12*1, Visor optional
WW-01A-8 300mm	W37*H28.7mm	8 W	>80	Mono(2700-6000K) R/G/B/A	544 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	3*1, Visor optional
WW-01A-18 1000mm	W37*H28.7mm	18 W	>80	Mono(2700-6000K) R/G/B/A	1224 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	18*1, Visor optional
WW-01A-9 500mm	W37*H28.7mm	9 W	>80	Mono(2700-6000K) R/G/B/A	612 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	9*1, Visor optional
WW-01A-6 300mm	W37*H28.7mm	6 W	>80	Mono(2700-6000K) R/G/B/A	408 LM	20°,30°,40°,60° 20x40° ,18x50°	DC24V	ON/OFF	6*1, Visor optional
WW-01A-36 1000mm	W37*H28.7mm	36 W	/	chromatic (RGB or RGBW)	1404 LM	15°20°30°45°60°25x45°	DC24V	DMX	36*1, Visor optional
WW-01A-18 500mm	W37*H28.7mm	18 W	/	chromatic (RGB or RGBW)	702 LM	15°20°30°45°60°25x45°	DC24V	DMX	18*1, Visor optional
WW-01A-12 300mm	W37*H28.7mm	12 W	/	chromatic (RGB or RGBW)	468 LM	15°20°30°45°60°25x45°	DC24V	DMX	12*1, Visor optional
WW-01A-24 1000mm	W37*H28.7mm	24 W	/	chromatic (RGB or RGBW)	936 LM	15°20°30°45°60°25x45°	DC24V	DMX	24*1, Visor optional
WW-01A-12 500mm	W37*H28.7mm	12 W	/	chromatic (RGB or RGBW)	468 LM	15°20°30°45°60°25x45°	DC24V	DMX	12*1, Visor optional
WW-01A-8 300mm	W37*H28.7mm	8 W	/	chromatic (RGB or RGBW)	312 LM	15°20°30°45°60°25x45°	DC24V	DMX	3*1, Visor optional

✦ Notes:

1. Finish: Gray, and customized RAL available.
2. Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K) , Tunable White (2700K~5000K), Chromatic (RGB, RGBW)
3. This lamp with 18-24W/M for Non-dim, and with 24-36W/M for Dim.