

▼ 1616



▼ Characteristic

Neon Flex Three Side Top Bend: Effortless Brilliance

1. Flexible & Easy Install: Installs whole or cuts to size for customization (maintains IP67 rating) - no extra parts needed.
2. Durable & Weatherproof (IP67): Eco-friendly, UV-resistant silicone construction ensures long-lasting vibrancy and withstands harsh environments.
3. Uniform Linear Illumination: Three-sided light emission delivers consistent brightness across the entire length.
4. High Light Transmittance: Up to brighter for exceptional illumination.

▼ Application

I+Infrastructure: Airport ,Railway Station ,Bridge , Municipal building ,Tunnel

I+Urban: Administrative Building , Commercial Building , Hotel , Mall

I+Cultural and Entertainment: Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC




▼ Technical Data

Model	SIZE (mm)	BENDING DIRECTION	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/M)	VOLT	Control	CUTTING (mm)	Remark
NEON-02C	16*16mm	Top Bending (Φ > 80-120mm)	6/8/10	>80	Mono 2700-6000K	420~700	DC24V	ON/OFF	50	standard 3pc clips/M
NEON-02C	16*16mm	Top Bending (Φ > 80-120mm)	6/8/10	>80	Tunable white 2700-6000K	420~700	DC24V	DMX	50	standard 3pc clips/M
NEON-02C	16*16mm	Top Bending (Φ > 80-120mm)	6/8/10	/	chromatic (RGB or RGBW)	200~300	DC24V	DMX	50	standard 3pc clips/M

Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K, Red, Green, Blue, Amber), Tunable White (2700K~5000K), Chromatic (RGB, RGBW)

▼ Installation Method

1. Surface Mounted
2. Recessed Mounted



▼ Outlet Method

