



▼ Characteristic

- Premium Materials**
 - Die-cast stainless steel body for excellent durability and corrosion resistance.
 - 316 stainless steel front panel for superior saltwater and chemical resistance.
 - Nickel-plated brass cable gland ensures enhanced waterproof performance.
- Rated IP68** for full submersion in water, providing reliable long-term underwater operation.
- Optimized structure** for excellent heat management and extended lifespan.
- Modern design** suitable for fountains, pools, aquariums, and underwater landscape lighting.
- High-performance LED light source** with low power consumption and reduced maintenance costs.

▼ Application

- Infrastructure:** Bridge underwater lighting, Riverfront landscaping, Civic landscape projects, Urban water features, Artificial lakes.
- Urban:** City squares, Public parks, Garden ponds, Outdoor fountains, Waterfalls.
- Cultural and Entertainment:** Resort pools and water displays, Hotel landscaping, Golf course water features, Outdoor aquatic theme parks, Zoo and aquarium outdoor water areas.



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data (full sery)

| Model | SIZE (mm) | POWER (W/M) | CRI | CCT (K) | LUMINOUS (LM/W) | B.angle | VOLT | Control | N.G | Remark |
|-----------|-------------|-------------|------|-------------------|-----------------|--------------------------------|----------|---------|-----|--------|
| UW-01A-54 | φ250XH126mm | 54 W | > 80 | 3000K-5700K | 80 LM/W | 10/15/20/30/60/100° | DC12/24V | ON/OFF | / | / |
| UW-01A-45 | φ250XH126mm | 45 W | > 80 | 3000-5700K | 100 LM/W | 15/25/36/60° | DC12/24V | ON/OFF | / | / |
| UW-01A-36 | φ250XH126mm | 36 W | > 80 | 3000-5700K | 64 LM/W | 10/15/20/30/60/100° /25x45° | DC12/24V | ON/OFF | / | / |
| UW-01A-54 | φ250XH126mm | 54 W | / | Chromatic (RGB) | 33 LM/W | 25/40/60° | DC12/24V | DMX512 | / | / |
| UW-01A-54 | φ250XH126mm | 54 W | / | Chromatic (RGBW) | 46 LM/W | 25/40/60° | DC12/24V | DMX512 | / | / |
| UW-01A-54 | φ250XH126mm | 54 W | / | Chromatic (R+G+B) | 60 LM/W | 15/25/40/60° | DC12/24V | DMX512 | / | / |

I+Notes:

1. Finish: Natural stainless steel color, and customized RAL available.
2. Notes: Mono (3000K,3500K,4000K,4500K,5700K) , Chromatic (RGB, RGBW).