
RIDILUX

LED UNDERWATER LIGHT





- 1.Premium Materials
- -Die-cast stainless steel body for excellent durability and corrosion resistance.
- -316 stainless steel front panel for superior saltwater and chemical resistance.
- -Nickel-plated brass cable gland ensures enhanced waterproof performance.
- 2.Rated IP68 for full submersion in water, providing reliable long-term underwater operation.
- 3. Optimized structure for excellent heat management and extended lifespan.
- 4. Modern design suitable for fountains, pools, aquariums, and underwater landscape lighting.
- 5. High-performance LED light source with low power consumption and reduced maintenance costs.



▼ Application



I+Infrastructure: Bridge underwater lighting, Riverfront landscaping, Civic landscape projects, Urban water features, Artificial lakes.

I+Urban: City squares, Public parks, Garden ponds, Outdoor fountains, Waterfalls.

I+Cultural and Entertainment: Resort pools and water displays, Hotel landscaping, Golf course water features, Outdoor aquatic theme parks, Zoo and aquarium outdoor water areas.



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is availble, Pls confirm before ordering.









ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data (full serv)

Model	SIZE (mm)	POWER (W/M)	CRI	ССТ (К)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
UW-02B-24	φ182XH65mm	24 W	> 80	3000K-5700K	81 LM/W	10/25/40/60/10x30/10x60°	DC12/24V	ON/OFF	/	/
UW-02B-30	φ182XH65mm	30 W	1	Chromatic (RGB)	30 LM/W	25/40/60/10x30/10x60°	DC12/24V	DMX512	/	/
UW-02B-42	φ182XH65mm	42 W	1	Chromatic (RGBW)	30 LM/W	25/40/60/10x30/10x60°	DC12/24V	DMX512	/	/
UW-02B-18	φ182XH65mm	18 W	> 80	3000K-5700K	81 LM/W	10/25/40/60/10x30/10x60°	DC12/24V	ON/OFF	/	/
UW-02B-22.5	φ182XH65mm	23 W	1	Chromatic (RGB)	30 LM/W	25/40/60/10x30/10x60°	DC12/24V	DMX512	/	/
UW-02B-31.5	φ182XH65mm	32 W	1	Chromatic (RGBW)	30 LM/W	25/40/60/10x30/10x60°	DC12/24V	DMX512	/	/

I+Notes:

- 1. Finish: Natural stainless steel color, and customized RAL available.
- $2. \ Notes: Mono \ (3000K, 3500K, 4000K, 4500K, 5700K) \ , \ Chromatic \ (RGB, RGBW).$