

## ▼ Characteristic

1. Premium Materials
  - Die-cast stainless steel body for excellent durability and corrosion resistance.
  - 316 stainless steel front panel for superior saltwater and chemical resistance.
  - Nickel-plated brass cable gland ensures enhanced waterproof performance.
2. Rated IP68 for full submersion in water, providing reliable long-term underwater operation.
3. Optimized structure for excellent heat management and extended lifespan.
4. Modern design suitable for fountains, pools, aquariums, and underwater landscape lighting.
5. High-performance LED light source with low power consumption and reduced maintenance costs.


## ▼ Application

- ↳ **Infrastructure:** Bridge underwater lighting, Riverfront landscaping, Civic landscape projects, Urban water features, Artificial lakes.
- ↳ **Urban:** City squares, Public parks, Garden ponds, Outdoor fountains, Waterfalls.
- ↳ **Cultural and Entertainment:** Resort pools and water displays, Hotel landscaping, Golf course water features, Outdoor aquatic theme parks, Zoo and aquarium outdoor water areas.

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



**ON/OFF 0-10V DALI DMX TRIAC**



Standard without recessed box



## ▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
UW-03A-12	L328XW63X75mm	12 W	> 80	3000K-5700K	80 LM/W	25/40/60°	DC12/24V	ON/OFF	/	/
UW-03A-18	L328XW63X75mm	18 W	/	Chromatic (RGB)	21 LM/W	25/40/60°	DC12/24V	DMX512	/	/
UW-03A-24	L328XW63X75mm	24 W	/	Chromatic (RGBW)	22 LM/W	25/40/60°	DC12/24V	DMX512	/	/
UW-03B-6	L195XW63X75mm	6 W	> 80	3000K-5700K	80 LM/W	25/40/60°	DC12/24V	ON/OFF	/	/
UW-03B-9	L195XW63X75mm	9 W	/	Chromatic (RGB)	21 LM/W	25/40/60°	DC12/24V	DMX512	/	/
UW-03B-12	L195XW63X75mm	12 W	/	Chromatic (RGBW)	22 LM/W	25/40/60°	DC12/24V	DMX512	/	/

### ↳ Notes:

1. Finish: Natural stainless steel color, and customized RAL available.
2. Notes: Mono (3000K,3500K,4000K,4500K,5700K) , Chromatic (RGB, RGBW).