



Standard without visor

## ▼ Charaterastic

- ✦ The hidden structure design is perfectly combined with the curtain wall, and the transmission signal of the lamp adopts the dual-wire parallel control technology.
- ✦ Aluminum housing ,ultra white tempered safety glass, lens -PMMA; vertically tilt mounting bracket;
- ✦ Akzonobel anti-UV polyester powder, outdoor grade spray or oxidation treatment, UV protection for 5 years.
- ✦ Surface mounting.
- ✦ Working temperature is -50°C to 70°C

## ▼ Application

- I+ **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel
- I+ **Urban:** Administrative Building , Commercial Building , Hotel , Mall
- I+ **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



**ON/OFF 0-10V DALI DMX TRIAC**

## ▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
LL-02A	L1000*W27.2*H50.5mm	12 W	> 80	Mono 2700-6500K	80 LM/W		DC24V	ON/OFF	/	/
LL-02A	L1000*W27.2*H50.5mm	12 W	> 80	Tunable white 2700-6000K	80 LM/W		DC24V	DMX512	/	/
LL-02A	L1000*W27.2*H50.5mm	12/15/18	/	chromatic (RGB or RGBW)	45 LM/W		DC24V	DMX512	/	/
LL-02B	L500*W27.2*H50.5mm	6 W	> 80	Mono 2700-6500K	80 LM/W		DC24V	ON/OFF	/	/
LL-02B	L500*W27.2*H50.5mm	6 W	> 80	Tunable white 2700-6000K	80 LM/W		DC24V	DMX512	/	/
LL-02B	L500*W27.2*H50.5mm	6/7.5/9	/	chromatic (RGB or RGBW)	45 LM/W		DC24V	DMX512	/	/
LL-02C	L300*W27.2*H50.5mm	4 W	> 80	Mono 2700-6500K	80 LM/W		DC24V	ON/OFF	/	/
LL-02C	L300*W27.2*H50.5mm	4 W	> 80	Tunable white 2700-6000K	80 LM/W		DC24V	DMX512	/	/
LL-02C	L300*W27.2*H50.5mm	4/4.75/6	/	chromatic (RGB or RGBW)	45 LM/W		DC24V	DMX512	/	/

### I+ Notes:

1. Finish: Gray, and customized RAL available.
2. Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K) , Chromatic (RGB, RGBW).
3. This lamp with 12W/M for Non-dim & Dim.