





Up&Down Side



Down Side



▼ Characteristic

- Superior Optical Performance**
 - High-efficiency LED with precise beam control, offering multiple beam angles and color temperatures (2700K/3000K/4000K).
 - Glare-free design for uniform and comfortable illumination.
- Durable and Reliable**
 - Die-cast aluminum housing with corrosion-resistant coating, suitable for indoor and outdoor use.
 - IP65 waterproof and IK05 impact-resistant for long-lasting performance.
- Easy Installation**
 - Supports recessed, surface-mounted, and wall-mounted options for versatile applications.
 - Lightweight design for hassle-free installation.
- Smart Control**
 - Compatible with DALI, DMX512, and 0-10V for dimming and dynamic lighting effects.
 - Sensor integration available for intelligent energy-saving solutions.

▼ Application

Architectural façades, Landscape lighting, Commercial spaces, and Residential settings etc.



ON/OFF 0-10V DALI DMX TRIAC

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.

▼ Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WL-03B-36	F75xW98xH240	26 W	> 80	2700K-6000K	83 LM/W	3/8/18/22/30/60°	AC220V	ON/OFF	/	Up&down
WL-03B-15	F75xW98xH170	15 W	> 80	2700K-6000K	83 LM/W	3/8/18/22/30/60°	AC220V	ON/OFF	/	Down

↳ Notes:

1. Finish: Black, and customized RAL available
2. It has four size with 4 different watt from 5W-36W.

▼ Simulation



▼ Project



▼ Photometric curve

