



▼ Characteristic

1. Exceptional Lighting Performance
 - High-efficiency LED delivers uniform, linear illumination.
 - Multiple beam angles for versatile lighting needs.
 - Glare-free optics ensure maximum visual comfort.
2. Durable and Weather-Resistant
 - Die-cast aluminum housing with corrosion-resistant coating.
 - IP65 waterproof and IK05 impact-resistant, perfect for outdoor use.
 - Tempered glass cover offers superior scratch and impact protection.
3. Effortless Installation
 - Compact, sleek design blends seamlessly with architectural elements.
 - Supports recessed or surface mounting for quick and easy setup.
4. Energy-Efficient and Sustainable
 - Low energy consumption with a lifespan exceeding 50,000 hours.
 - Environmentally friendly and low maintenance.

▼ Application

I+ Outdoor Occasion such as window sills, ledges, and architectural details in residential, commercial, and public spaces etc.

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WIN-02B-12	L200xW60xH60mm	12 W	> 80	3000K-5700K	82 LM/W	3x180°	DC24V	ON/OFF	/	/
WIN-02B-18	L200xW60xH60mm	18 W	/	Chromatic (RGB)	45 LM/W	3x180°	DC24V	DMX512	/	/
WIN-02B-18	L200xW60xH60mm	18 W	/	Chromatic (RGBW)	45 LM/W	3x180°	DC24V	DMX512	/	/

I+ Notes:

1. Finish: Black, and customized RAL available
2. It has three size from 6W-18W.

▼ Simulation



▼ Project



▼ Photometric curve

