



Standard without visor

▼ Characteristic

- ✦ The hidden structure design is perfectly combined with the curtain wall, and the transmission signal of the lamp adopts the dual-wire parallel control technology.
- ✦ Aluminum housing ,ultra white tempered safety glass, lens -PMMA; vertically tilt mounting bracket;
- ✦ Akzonobel anti-UV polyester powder, outdoor grade spray or oxidation treatment, UV protection for 5 years.
- ✦ Surface mounting.
- ✦ Working temperature is -50°C to 70°C

▼ Application

- ✦ **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel
- ✦ **Urban:** Administrative Building , Commercial Building , Hotel , Mall
- ✦ **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, PIs confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WW-04A-48	L1000xW54xH32mm	48 W	> 80	3000K-5700K	80 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	ON/OFF	/	/
WW-04A-60	L1000xW54xH32mm	60 W	/	Chromatic (RGB)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/
WW-04A-80	L1000xW54xH32mm	80 W	/	Chromatic (RGBW)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/
WW-04B-24	L500xW54xH32mm	24 W	> 80	3000K-5700K	80 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	ON/OFF	/	/
WW-04B-30	L500xW54xH32mm	30 W	/	Chromatic (RGB)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/
WW-04B-30	L500xW54xH32mm	30 W	/	Chromatic (RGBW)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/
WW-04C-8	L300xW54xH32mm	8 W	> 80	3000K-5700K	80 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	ON/OFF	/	/
WW-04C-24	L300xW54xH32mm	24 W	/	Chromatic (RGB)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/
WW-04C-24	L300xW54xH32mm	24 W	/	Chromatic (RGBW)	45 LM/W	3/5/10/15/30/45/60/10x30°	AC85-265V	DMX512	/	/

✦ Notes:

1. Finish: Gray, and customized RAL available.
2. Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K) , Chromatic (RGB, RGBW).
3. This lamp with 48W/M for Non-dim & Dim.