


## ▼ Characteristic



- ✦ The hidden structure design is perfectly combined with the curtain wall, and the transmission signal of the lamp adopts the dual-wire parallel control technology.
- ✦ Aluminum housing ,ultra white tempered safety glass, lens -PMMA; vertically tilt mounting bracket;
- ✦ Akzonobel anti-UV polyester powder, outdoor grade spray or oxidation treatment, UV protection for 5 years.
- ✦ Surface mounting.
- ✦ Working temperature is -50°C to 70°C

## ▼ Application

Standard without visor

✦ **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel

✦ **Urban:** Administrative Building , Commercial Building , Hotel , Mall

✦ **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site



▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



**ON/OFF 0-10V DALI DMX TRIAC**

## ▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WW-05A-108	L1000xW90xH53mm	108 W	> 80	3000K-5700K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	ON/OFF	/	/
WW-05A-108	L1000xW90xH53mm	108 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/
WW-05A-144	L1000xW90xH53mm	144 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/
WW-05B-54	L500xW90xH53mm	54 W	> 80	3000K-5700K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	ON/OFF	/	/
WW-05B-54	L500xW90xH53mm	54 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/
WW-05B-72	L500xW90xH53mm	72 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/
WW-05C-36	L300xW90xH53mm	36 W	> 80	3000K-5700K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	ON/OFF	/	/
WW-05C-36	L300xW90xH53mm	36 W	/	Chromatic (RGB)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/
WW-05C-36	L300xW90xH53mm	48 W	/	Chromatic (RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	AC85-265V	DMX512	/	/

### ✦ Notes:

1. Finish: Gray, and customized RAL available.
2. Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K) , Chromatic (RGB, RGBW).
3. This lamp with 108W/M for Non-dim & Dim.