



Standard without visor



▼ Characteristic

- ✦ The hidden structure design is perfectly combined with the curtain wall, and the transmission signal of the lamp adopts the dual-wire parallel control technology.
- ✦ Aluminum housing ,ultra white tempered safety glass, lens -PMMA; vertically tilt mounting bracket;
- ✦ Akzonobel anti-UV polyester powder, outdoor grade spray or oxidation treatment, UV protection for 5 years.
- ✦ Surface mounting.
- ✦ Working temperature is -50°C to 70°C

▼ Application

- ✦ **Infrastructure:** Airport ,Railway Station ,Bridge , Municipal building ,Tunnel
- ✦ **Urban:** Administrative Building , Commercial Building , Hotel , Mall
- ✦ **Cultural and Entertainment:** Pavilion , Plaza ,Village ,Amusement park ,Monuments ,Cathedral ,Heritage site

▼ "Non-dim/dim" and "Mono/Tunable white/chromatic" is available, Pls confirm before ordering.



ON/OFF 0-10V DALI DMX TRIAC

▼ Technical Data (full sery)

Model	SIZE (mm)	POWER (W/M)	CRI	CCT (K)	LUMINOUS (LM/W)	B.angle	VOLT	Control	N.G	Remark
WW-02A-24	L1000*W40.5*H77mm	24/36/48	> 80	Mono 2700-6500K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	ON/OFF	/	/
WW-02A-48	L1000*W40.5*H77mm	24/36/48	/	Tunable white 2700-6000K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/
WW-02A-48	L1000*W40.5*H77mm	24/36/48	/	chromatic (RGB or RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/
WW-02B-12	L500*W40.5*H77mm	12/18/24	> 80	Mono 2700-6500K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	ON/OFF	/	/
WW-02B-24	L500*W40.5*H77mm	12/18/24	/	Tunable white 2700-6000K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/
WW-02B-24	L500*W40.5*H77mm	12/18/24	/	chromatic (RGB or RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/
WW-02C-8	L300*W40.5*H77mm	8/12/16	> 80	Mono 2700-6500K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	ON/OFF	/	/
WW-02C-16	L300*W40.5*H77mm	8/12/16	/	Tunable white 2700-6000K	80 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/
WW-02C-16	L300*W40.5*H77mm	8/12/16	/	chromatic (RGB or RGBW)	45 LM/W	5/10/15/30/45/60/15x45 /10x60°	DC24V	DMX512	/	/

✦ Notes:

1. Finish: Gray, and customized RAL available.
2. Notes: Mono (2700K,3000K,3500K,4000K,4500K,5000K) , Chromatic (RGB, RGBW).
3. This lamp with 24-48W/M for Non-dim & Dim.